


Stratus® ftServer® 2510 System

The Stratus® ftServer® 2510 system makes industry-leading 99.999% uptime highly affordable to purchase, quick to deploy, simple to manage, and cost-effective to own. The most economical, most compact fault-tolerant server on the market today, the 2510 model brings you a compelling new choice for decentralized, mission-critical applications. Priced below comparable high-availability clusters, these servers combine economic value with *lights-out* management capabilities, making them ideal for volume deployment at remote locations — or as fault-tolerant replacements for ordinary, standalone servers.



Total Availability



Operational Simplicity



Financial Advantage

Powered by the quad-core Intel® Xeon® processor, the 2510 model features the Microsoft® Windows Server™ 2003 or the Red Hat® Enterprise Linux® 5 operating system. Every Stratus 2510 system delivers Continuous Processing® technology at breakthrough pricing — thanks to a streamlined design that takes advantage of industry-standard components.

The 2510 model is available in a pedestal version or a 4U rack-mount model that installs in a standard rack. These new entry-level systems enable affordable rollouts at locations with limited IT support: remote distribution hubs, branch banks, retail stores, and other sites requiring rapid, effortless deployment and near zero downtime.

Continuous Processing® features

Like other members of the industry-standard ftServer family, the 2510 model comes complete with Continuous Processing features that eliminate operational complexity and high costs inherent in clusters or standby systems. Your enterprise gains superior uptime protection without having to modify applications — and without the need for failover scripting, repeated test procedures, or extra effort to make your applications cluster-aware.



Lockstep technology

Replicated, fault-tolerant hardware components process the same instructions at the same time. In the event of a component malfunction, the partner component is an active spare that continues normal operation without system downtime or data loss.

Failsafe software

Our failsafe software works in concert with lockstep technology to prevent software errors from escalating into outages. Other software issues are captured, analyzed, and reported to Stratus. This allows support personnel to take a proactive approach to correcting software problems before they recur. Even in-memory data is constantly protected and maintained. Stratus' hardened device drivers add yet another level of reliability to the operating system environment on ftServer systems.

ActiveService™ architecture

ftServer systems constantly monitor their own operation. Remote support capabilities — made possible by the global Stratus ActiveService Network — enable our service engineers to diagnose, troubleshoot, and resolve problems online as if they were on-site. If needed, the system automatically orders its own hot-swappable replacement part.



ftServer 2510 systems:
99.999% uptime,
breakthrough price,
rapid deployment, and
lights-out management



The Smarter Approach to Uptime™

With the 2510 system, you don't have to choose between maximum uptime protection and low price. Stratus brings continuous availability and affordability together in a server that is ideal for volume deployment at remote locations.



ftServer 2510 system specifications

PROCESSORS	
Logical processor	1-socket
Processor	Quad-core Intel® Xeon® processor 2.00 GHz
Cache	2 x 6MB
Front side bus	1333 MHz
MEMORY	
Min/max memory	2 GB/ 6 GB DDR2 667 MHz FBDIMM
I/O SUBSYSTEM	
PCI slots user configurable	6 PCI-X; or 2 PCI-Express and 4 PCI-X
STORAGE SUBSYSTEM	
Internal disk drives supported	500 GB (7200 RPM) SATA 146 GB; 300 GB (15K RPM) SAS
Base system drive slots	6
ftSCALABLE STORAGE SUBSYSTEM	
Expansion drive slots (SAS)	36
RAID Levels	0, 1, 3, 5, 6, 10, 50
EMBEDDED I/O	
10/100/1000 Ethernet	2 dual port
DISK	3 internal channels
DVD-R/W	2
Serial port	2
USB port	3
MANAGEABILITY	
Baseboard Management Controller	standard
Virtual Technician Module (VTM)	2 optional
PCI ADAPTERS	
Fibre Channel	up to 4 optional
1000 Base-T/SX dual port Ethernet	up to 6 optional
Ultra320 tape	up to 2 optional
SERVICEABILITY	
Hot-swappable components	CPU / I/O module, disks
OPERATING SYSTEMS	
Microsoft Windows®	Windows Server 2003 Standard Edition
Red Hat Linux	Red Hat Enterprise Linux 5
POWER AND PACKAGING	
Input voltage	Rack: 100 - 240 VAC; 50 Hz, 60 Hz Pedestal: 100 - 240 VAC; 50 Hz, 60 Hz
Rack system dimension (H x W x D)	7.0" (4U) x 17.5" x 30"
Pedestal system dimension (H x W x D)	23.25" x 12.88" x 31.38"
Weight (fully loaded)	Rack: 56.16 kg (123.8 lbs.) including rails Pedestal: 80.7 kg (178 lbs)

Specifications and descriptions are summary in nature and subject to change without notice. Stratus, ftServer, the ftServer logo, and Continuous Processing are registered trademarks and ActiveService, the Stratus Technologies logo, The Smarter Approach to Uptime, ftScalable, and the Stratus 24x7 logo are trademarks of Stratus Technologies Bermuda Ltd. Microsoft, Windows, Windows Server, and the Windows logo are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. The registered trademark Linux is used pursuant to a sublicense from the Linux Mark Institute, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis. Red Hat and the Red Hat Shadowman logo are registered trademarks of Red Hat, Inc. in the United States and other countries.