


Stratus® ftServer® 4400 System



Continuous Availability

The Stratus® ftServer® 4400 system brings leading price/performance and premier continuous availability to a mid-range server designed for computing environments built around the Microsoft® Windows Server™ 2003 and Red Hat® Enterprise Linux® 4 operating systems. Delivering 99.999% and greater uptime, this modular server harnesses the Intel® Xeon® processor to achieve high-performance processing power in an affordable 1- or 2-socket system.

The ftServer 4400 system is the perfect choice for space-constrained data centers, remote offices, and *lights-out* settings where business continuity is essential. Customers have rapidly adopted the 4400 architecture to support dedicated business processing solutions that include: public safety computer-aided dispatch (CAD), financial services ATM/POS, call/contact center, and manufacturing operations management.



Operational Simplicity

The versatile 4400 system is available in rack-optimized or pedestal packaging. This third-generation system builds on the impressive reliability of ftServer technology. Improvements in physical design and increased use of modular, industry-standard components are further enhanced by the availability, performance, and security features offered by the Windows Server 2003 and the Red Hat Enterprise Linux 4 operating systems.

Continuous Processing® features

Like other members of the industry-standard ftServer family, the model 4400 comes complete with Stratus Continuous Processing features that eliminate operational complexity and high costs inherent in high-availability approaches such as clusters. Your enterprise gains superior uptime protection without having to modify applications — and without the need for failover scripting, repeated test procedures, or extra effort to make your applications cluster-aware.



Financial Advantage



Lockstep technology

Replicated, fault-tolerant hardware components process the same instructions at the same time. In the event of a component malfunction, the partner component is an active spare that continues normal operation. There is no system downtime and no data loss.

Failsafe software

Our failsafe software works in concert with lockstep technology to prevent many software errors from escalating into outages. Other software issues are captured, analyzed, and reported to Stratus. This allows support personnel to take a proactive approach to correcting software problems before they recur. Even in-memory data is constantly protected and maintained. Stratus' hardened device drivers add yet another level of reliability to the operating system environment on ftServer systems.

ActiveService™ architecture

ftServer systems constantly monitor their own operation. Remote support capabilities — made possible by the global Stratus ActiveService Network — enable our service engineers to diagnose, troubleshoot, and resolve problems online as if they were on-site. If needed, the 4400 system automatically orders its own customer- or field-replaceable parts.



ftServer 4400 systems:
industry-leading uptime,
big performance for
Windows and Linux
applications



**The Smarter
Approach to Uptime™**

The ftServer 4400 system redefines price/performance for fault-tolerant departmental business processing. This mid-range server taps the power of the Intel Xeon processor, which features Hyper-threading – Intel's most advanced dual-processor technology.



ftServer 4400 system specifications

| PROCESSORS | |
|---|--|
| Logical processors | 1- or 2-socket |
| Processor | Dual core Intel® Xeon® processor 2.00 GHz |
| Cache | 4 MB L2 |
| Front side bus | 1333 MHz |
| MEMORY | |
| Min/max memory | 2 Gb/12 GB DDR2; 667 MHz FBDIMM |
| I/O SUBSYSTEM | |
| PCI slots | 6 PCI-X; or 2 PCI-Express and 4 PCI-X |
| STORAGE SUBSYSTEM | |
| Internal disk drives supported | 250 GB, 500 GB (7200 RPM) SATA 73 GB, 146 GB (15K RPM) SAS |
| Base system drive slots | 6 |
| ftSCALABLE STORAGE SUBSYSTEM | |
| Expansion drive slots (RAID) | 36 |
| RAID Levels | 0, 1, 3, 5, 10, 50 |
| EMBEDDED I/O | |
| 10/100/1000 Ethernet | 2 dual port |
| DISK | 3 internal channels |
| DVD-R/W | 2 |
| Serial port | 2 |
| USB port | 3 |
| MANAGEABILITY | |
| Baseboard Management Controller | standard |
| Virtual Technician Module (VTM) | 2 optional |
| PCI ADAPTERS | |
| Fibre Channel (Stratus ftScalable™ Storage) | 2 optional |
| Fibre Channel (EMC) | up to 4 optional (Windows only) |
| 1000 Base-T/SX dual port Ethernet | up to 6 optional |
| Ultra320 tape | up to 2 optional |
| SERVICEABILITY | |
| Hot-swappable components | CPU / I/O module, disks |
| OPERATING SYSTEMS | |
| Microsoft Windows | Windows Server 2003 Enterprise Edition |
| Linux® | Red Hat Enterprise Linux 4 (64-bit) |
| POWER AND PACKAGING | |
| Input voltage | Rack: 100-240 VAC; 50 Hz, 60 Hz Pedestal: 100-230 VAC; 50 Hz, 60 Hz |
| Rack system dimension (H x W x D) | 7.0" (4U) x 17.5" x 30" |
| Pedestal system dimension (H x W x D) | 23.25" x 12.88" x 31.38" |
| Weight (fully loaded) | Rack: 56.16 kg (123.8 lbs.) including rails |

Specifications and descriptions are summary in nature and subject to change without notice.

Stratus, ftServer, the ftServer logo, and Continuous Processing are registered trademarks and ActiveService, the Stratus Technologies logo, The Smarter Approach to Uptime, ftScalable, and the Stratus 24x7 logo are trademarks of Stratus Technologies Bermuda Ltd. Microsoft, Windows, Windows Server, and the Windows logo are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. The registered trademark Linux is used pursuant to a sublicense from the Linux Mark Institute, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis. Red Hat, Enterprise Linux, and the Red Hat Shadowman logo are registered trademarks of Red Hat, Inc. in the United States and other countries. Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.