



## BAT54-Rail

Industrial Networking:Industrial Ethernet:Wireless LAN:Chassis

Product description	
Description	Dualband Industrial Wireless LAN Access Point/Client with two independent radio modules with IEEE 802.11a/b/g/h/i
Port type and quantity	Two WLAN interfaces, up to 8 SSIDs per WLAN interface, two LAN ports 10/100BASE-TX, autosensing, Power over Ethernet according to IEEE 802.3af, IP40-housing
Type	BAT54-Rail
Order No.	943 926-001
Radio technology	
Antenna connector	four RP-SMA jack antenna connectors
Range	Up to 20km with external antenna (depending on type of antenna, frequency range and data rate)
Data rate	54 Mbps according to IEEE 802.11g (Fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), 802.11 b/g compatibility mode or pure g or pure b selectable. 54 Mbps according to IEEE 802.11a/h (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), Super A/G with Turbo Mode (108 MBps), Bursting, Compression, fully compliant to ETSI requirements with TPC and DFS
Encryption	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, user authentication by 802.1x /EAP or LEPS, IEEE 802.1x Supplicant in Client Mode, WPA/TKIP, WEP, access-control lists, WLAN port and protocol filter, RADIUS client and server, Built-in Firewall with QoS, port filter, protocol filter, IDS and DoS protection, PMK-Caching and Preauthentication for fast roaming with IEEE 802.1x
Operating system	LAN interface usable for simultaneous DSL-over-LAN, IP-Router, NAT/Reverse NAT (IP-Masquerading) DHCP-Server, DHCP-Client, DHCP-Relay-Server, DNS-Server, PPPoE-Client (incl. Multi-PPPoE), PPTP- Client und - Server, NetBIOSProxy, DynDNS-Client, NTP, Port-Mapping, Policy-based Routing on basis of Routing-Tags, Tagging according to firewall rules, dynamic routing RIPv2, VRRP, Rapid Spanning Tree Protocol (IEEE 802.1w), ARP, Proxy ARP, BOOTP, DHCP, DNS, HTTP, HTTPS, IP, ICMP, NTP/SNTP, NetBIOS, PPPoE (Server), RADIUS, RIP- 1, RIP-2, RTP, SIP, SNMP, TCP, TFTP, UDP, VRRP, VLAN with up to 4094 VLAN IDs for WLAN connections, 32 usable simultaneously, dynamic VLAN-Tags for 802.1x-Clients, Integrated RADIUS server with IEEE 802.1x/EAP authentication
Frequency band	two independent radio modules, each 2.4GHz and 5GHz: 2400-2483,5 MHz (ISM) and 5150-5850 MHz
Modulation	22M0F7D(DSSS/OFDM) at 2.4 GHz 20M0G7D (OFDM) at 5 GHz
Receiver sensitivity	2.4GHz 802.11b: -87dBm @ 1Mbit/s, -94dBm @ 1Mbit/s 2.4GHz 802.11g: -87dBm @ 6Mbit/s, -70dBm @ 54Mbit/s 5GHz 802.11a/h: -87dBm @ 6Mbit/s, -67dBm @ 54Mbit/s
Radio topology	WLAN Access Point, Bridge, Router, Point-to-Point, Client, Client-Bridge Mode, fixed mesh with RSTP
Roaming	Seamless handover between radio cells, IAPP support, IEEE 802.11d support, Background scanning for rogue AP detection and fast roaming, Support of IEEE 802.11e (WME), preauthentication and PMK caching with IEEE 802.1x

Radio Power 2.4 GHz 802.11b: +19dBm @ 1 and 2 Mbps, +19dBm @ 5.5 and 11Mbps, 2,4 GHz 802.11g: +19dBm @ 6Mbps, +14dBm @ 54 Mbps, 5GHz 802.11a/h: +18dBm @ 6Mbps, +12 dBm @ 54 Mbps with TPC and DFS, Power Reduction in 1dB steps down to 0.5dBm minimum

### Power requirements

Operating voltage 2 \* 24V DC; 12V DC external Power Supply (230V)  
2x Power-over-Ethernet according to IEEE802.3af; all power supplies redundant to each other

Current consumption at 24 V DC 417mA

Current consumption 12V DC: 625mA; 24V DC: 417 mA; PoE (48V DC): 167 mA

### Service

Diagnostics Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, LANmonitor status display, internal logging buffer for SYSLOG and firewall events, monitor mode for Ethernet ports, WLANmonitor for WLAN network overview and Rogue AP detection

Management SNMP management via SNMP V2, private MIB exportable by WEBconfig, MIB II Remote configuration with Telnet/SSL, SSH, browser (HTTP/HTTPS), TFTP or SNMP, firmware upload via HTTP/HTTPS or TFTP  
Support of up to 4094 VLAN IDs for WLAN connections, 256 simultaneously usable VLAN tags for 802.11 clients

Other services Warning via e-mail, SNMP-Traps and SYSLOG; Remote management and configuration by modem support via LAN (DSL) or serial port

### Ambient conditions

Operation temperature -20° up to +50° (temporarily up to +70°C according to EN50155)

Storage/transport temperature -20°C to 70°C

Relative humidity (non-condensing) max. 95%

MTBF 43.3 years

### Mechanical construction

Dimensions (W x H x D) 80mm x 100mm x 135mm

Mounting for wall and Din Rail mounting

### Approvals

Safety of information technology equipment EN 60950

Radio EN 300328, EN 301893, notified in all countries of EU.  
For other notifications or certifications please refer to INET-Sales@hirschmann.de

Environmental EN 61131 for operation in automation environment  
EN 50155 for operation in vehicles  
EMC approval for E1 certification (cars and vehicles) available

### Scope of delivery and accessories

Scope of delivery device, CD, serial cable, Ethernet cable 3m, two 3-dBi-Dipol - Dualband antennas, two 50Ohm terminators, Rail mount material

Accessories to order separately external antennas for 802.11b/g and 802.11a/h operation  
adapter cable and surge arrestor